

VR1370

A.M. Ramp & Co GmbH, Druckfarbenfabrik
 Lorsbacher Str. 28, D-65817 Eppstein, Germany
 PB 100, D-65814 Eppstein, Germany
 Telefax: +49 6198 322 88 Phone: +49 6198 304 0
 internet: http://www.ruco.de ... e-mail: info@ruco-inks.com

Trade name : 100-VR-1370

Product identification : Organic solvent or solvent mixture

2. HAZARDOUS INGREDIENTS

Ingredient	CAS-Nr.	Concentration[%]	Symbol	R-phrased(for 100%)
Butylglycolacetate	112-07-2	20 ... 50	Xn	20/21
Cyclohexanone	108-94-1	20 ... 50	Xn	10-20

3. HAZARDS IDENTIFICATION

Human health (See also section #15)

- Inhalation : Excessive breathing of vapours has narcotic effects, may cause drowsiness.
- Skincontact: Degreasing effects. Prolonged or repeated contact may cause inflammation.
- Eyecontact : Moderate irritation by direct contact.
- Swallowing : Not known.

Environment : Harmful for aquatic environment.

In case of fire may be formed: carbonmonoxide/carbondioxide

4. FIRST AID MEASURES

Inhalation : Take victim to fresh air. Remove contaminated clothing.

Skincontact: Dab with soft tissue and wash with plenty of water and soap.
Do not use any organic solvent.

Eyecontact : Immediately rinse with plenty of water, keep eyelid lifted.
In case of irritation see physician.

Swallowing : On vomiting lie person on their side and keep respiratory tract free. See physician. Do not induce vomiting.

5. FIRE FIGHTING MEASURES

Extinguishing media: Foam, carbondioxide, waterspray

Unsuitable media: Waterjet

Hint : Do not allow extinguishing agent to soak into soil.

Take measures to collect contaminated firefighting agents.

Do not breathe vapours/fumes - use self-contained breathing apparatus.

=====
 This information is accurate to the best of our knowledge however is furnished without expressed or implied warranty.

 6. ACCIDENTAL RELEASE MEASURES

Person : Avoid contact with skin, eyes and clothes. Remove sources of ignition. Proper ventilation of workplace.

Environment : Prevent material to enter soil, drains or water courses.

Spill control: Absorb with sand, kieselguhr or other inert material.

For disposal fill in adequate containers and handle as special waste. See also section #13.

7. HANDLING AND STORAGE

Handling : Avoid release of vapours. Be sure to apply good room ventilation . Do not eat, drink or smoke at the workplace.

Storage : Keep container well closed after use. Avoid frequent warming above 50 °C.
Keep away from food. Preferably store in original container.

Hints : Product is flammable and can form combustible mixtures with air. Avoid electrostatic charging of container.

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Exposure : Install proper room ventilation in working- and storage area.

Respiratory : No special requirements with good room ventilation.

Eyes : When splashes may occur (pouring material into an other container) wear splash proof goggles.

Skin : Apply mild handcream. Use suitable protective gloves.
(i.e. neoprene or polyvinyl alcohol)

General : When handling the product wear usual protective work clothes.

9. PHYSICAL AND CHEMICAL PROPERTIES

pH-Value.....: n.a.

Appearance.....: liquid

Boilingpoint at.....[°C]: 156.0

Odour.....: characteristic

Flashpoint at.....[°C]: 43 (closed cup)

Shade.....: -

Ignitiontemperature at.....[°C]: 325

Supporting fire.....: by solvents

Lower explosion limit.....[Vol%]: 1.0

Upper explosion limit.....[Vol%]: 9.8

Solubility in water.....: 0% fully soluble components

Viscosity.....: 12sec in DIN-4-cup

Vapour pressure.....[mbar]: 4.5 (most volatile component)

Density.....[g/ml at 20°C]: 0.94

10. STABILITY AND REACTIVITY

Elevated temperature in the container may cause combustion.
(Increase of vapour pressure).

Direct contact with oxidants will yield decomposition/inflammation, liberating gases. Dangerous decomposition products: see #3.

This information is accurate to the best of our knowledge however is furnished without expressed or implied warranty.

=====

11. TOXICOLOGICAL INFORMATION

Ingredient	CAS-Nr.	Concentration[%]	MAK-Value [ppm]
Butylglycolacetate	112-07-2	20 ... 50	20
Cyclohexanone	108-94-1	20 ... 50	20

Excessive vapour concentration may yield narcotic effects.

12. ECOLOGICAL INFORMATION

The product can be biologically diminished.

Do not allow product to enter drains, groundwater or water courses.

13. DISPOSAL CONSIDERATIONS

EWC-Disposalcode (Other solvents and solventmixtures): 14 01 03 / proposal
Liquid remainder is special waste. Do not dispose together with normal
domestic waste. See local regulations.

Send via licensed waste handler to dump, incineration or redistillation in
accordance with local regulations.

Dry remainders may be disposed as domestic waste.

Emptied, cleaned and dry containers can be recycled.

14. TRANSPORT INFORMATION

VbF: Gefahrklasse A II

ADR/GGVS: class 3 / no. 31c, ADR

ADR/GGVS: 1263, paint related material. Contains: Cyclohexanone

UN/ID : 1263

IMDG: class 3.3

Marinepollutant: - -

EMS-Nr: 3-05

MFAG : 330

IATA: class 3

=====

This information is accurate to the best of our knowledge however is furnished
without expressed or implied warranty.

=====

15. REGULATORY INFORMATION

Flammability.....: R 10: Flammable

Health risk.....: Xn Harmful

Contains: Butylglycolacetate Cyclohexanone

R-phrases:

R 20: Harmful by inhalation

R 21: Harmful in contact with skin

S-phrases:

S7/9: Keep container tightly closed and in a well-ventilated place

S 16: Keep away from sources of ignition - No smoking

S 29: Do not empty into drains

S 35: This material and its container must be disposed of in a safe way

TA-air :

0 % class I

> 50 % class II

20...50 % class III

WGK (VwVwS): 1

16. OTHER INFORMATION

Contents of organic solvents at 100 %

Explanation:

n.a. = not applicable

n.b. = not known

n.m. = not measurable

* = for organic solvents

=====

This information is accurate to the best of our knowledge however is furnished without expressed or implied warranty.